

# Exhaust stock range

od	Wall	kg/m	304	304perf	409	409perf
28.58	1.2	0.82	•	•	•	•
28.58	1.5	1.02	•		•	
31.75	1.2	0.92	•	•	•	•
31.75	1.5	1.13	•		•	
35	1	0.85	•			
35	1.2	1.01	•	•	•	•
35	1.5	1.26	•		•	
36	1	0.88	•			
38.1	1.2	1.11	•	•	•	•
38.1	1.5	1.37	•		•	
41.27	1.2	1.20	•	•	•	•
41.27	1.5	1.49	•		•	
44.45	1.2	1.30	•	•	•	•
44.45	1.5	1.61	•		•	
45	1	1.10	•			
45	1.2	1.31	•			
45	2	2.15	•		•	
47.6	1.2	1.39	•	•	•	•
47.6	1.5	1.73	•		•	
48	1.2	1.40	•		•	
50.8	1	1.25	•		•	
50.8	1.2	1.49	•	•	•	•
50.8	1.5	1.85	•		•	
50.8	2	2.44	•		•	
52	1	1.28	•			
52	1.2	1.52	•			
54	1.2	1.58	•	•	•	•
54	1.5	1.97	•		•	
57.15	1.2	1.68	•	•	•	•
57.15	1.5	2.09	•		•	
57.15	2	2.76	•		•	
60.3	1.2	1.77	•	•	•	•
60.3	1.5	2.21	•		•	
63.5	1	1.56	•		•	
63.5	1.2	1.87	•	•	•	•
63.5	1.5	2.33	•		•	
63.5	2	3.08	•			
70	1.2	2.06	•			
70	1.5	2.57	•		•	
76.2	1.2	2.25	•	•		
76.2	1.5	2.80	•		•	
80	1.2	2.36	•			
88.9	1.2	2.63	•			
88.9	1.5	3.28	•			
101.6	1.5	3.75	•			
114.3	1.5	4.23	•			
127	1.5	4.71	•			